

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188		
<small>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Washington Headquarters Service, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188) Washington, DC 20503.</small> PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) 03-05-2001		2. REPORT DATE Final		3. DATES COVERED (From - To) Jun 1997 Jan 2001	
4. TITLE AND SUBTITLE Experimental Study of the Effect of Electron Beam Quality on Free-Electron Laser Gain			5a. CONTRACT NUMBER		
			5b. GRANT NUMBER N000149710845		
			5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S) Ilan Ben-Zvi			5d. PROJECT NUMBER		
			5e. TASK NUMBER		
			5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Physics and Astronomy Department The State University of New York at Stony Brook Stony Brook NY 11794-3800			8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) The Research Foundation of the State University of New York SUNY Stony Brook W 5510 Melville Library Stony Brook NY 11794-3366			10. SPONSOR/MONITOR'S ACRONYM(S)		
			11. SPONSORING/MONITORING AGENCY REPORT NUMBER		
12. DISTRIBUTION AVAILABILITY STATEMENT Unrestricted					
DISTRIBUTION STATEMENT A Approved for Public Release Distribution Unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT The objective was the measurement of the single pass FEL known as the High-Gain, Harmonic Generation FEL. The HGHG approach utilizes a laser-seeded FEL to produce amplified, longitudinally coherent, Fourier-transform-limited output at a harmonic of the seed laser. In the experiment performed at the Accelerator Test Facility at Brookhaven National Laboratory, a seed CO ₂ laser at a wavelength of 10.6mm produced saturated, amplified FEL output at the second-harmonic wavelength, 5.3mm. The HGHG FEL was demonstrated successfully. The duration of the output pulse was measured using a second-harmonic intensity autocorrelator, and the coherence length was measured using an interferometer. We also measured the energy distribution of the electron beam after it exited the second undulator, observing behavior consistent with that is expected at saturation. The intensity of the harmonic components of the output at 2.65 mm and 1.77 mm were determined relative to that of the 5.3-mm fundamental. Finally, using a corrector magnet upstream of the radiator, steering effects on the trajectories of the electron and light beams were studied.					
15. SUBJECT TERMS Free-Electron Laser; High-Gain; Harmonic Generation; Coherence					
16. SECURITY CLASSIFICATION OF:			18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON	
a. REPORT	b. ABSTRACT	c. THIS PAGE		19b. TELEPHONE NUMBER (Include area code)	

Title of Research Effort

**EXPERIMENTAL STUDY OF THE EFFECT OF THE
ELECTRON BEAM QUALITY ON FREE-ELECTRON LASER GAIN**

PI Name

Ilan Ben-Zvi

State University of New York at Stony Brook

Department of Physics and Astronomy

Stony Brook

NY

11974-3800

Phone: (631) 344-5143

Fax: (631) 344-3029

Email: ilan@bnl.gov

Grant Number N000149710845

ONR Program Officer: Charles W. Roberson

Programs Long-term Research Objective:

Several configurations of an FEL source are possible. The most widespread configuration involves the use of a high-Q optical cavity and is very effective in wavelength regimes where appropriate mirrors are available. As in the case of lasers, use of an optical resonator can provide a high degree of spatial and temporal coherence. Conversely, the strategy for developing a hard x-ray FEL utilizes a high-gain, single-pass amplifier scheme to circumvent the lack of high quality resonator mirrors at short wavelengths. A straightforward approach to single-pass amplification is referred to as self-amplified spontaneous emission (SASE). In SASE, the spontaneous radiation emitted by quivering electrons near the beginning of a long undulator magnet is subsequently amplified as it co-propagates with the electron beam through the magnetic structure. This process is capable of producing output with high peak power and excellent spatial mode, but a limitation imposed by the random noise buildup is poor temporal coherence, i.e. coherence time much less than pulse duration.

In this research we investigated an alternative single-pass FEL approach, high-gain harmonic-generation (HGHG), capable of providing the intensity and spatial coherence of SASE but with excellent temporal coherence. In the HGHG FEL, a small energy modulation is imposed on the electron beam by interaction with a seed laser in a short undulator (the modulator). The energy modulation is converted to a coherent spatial density modulation as the electron beam traverses a dispersion magnet (a three-dipole chicane). A second undulator (the radiator), tuned to a higher harmonic of the seed frequency (ω), causes the micro-bunched electron beam to emit coherent radiation at the harmonic frequency ($n\omega$), followed by exponential amplification until saturation is achieved. The HGHG output radiation has a single phase determined by the seed laser and its spectral bandwidth is Fourier transform limited.

A major advantage of the HGHG FEL is that the output properties at the harmonic wavelength are a map of the characteristics of the high-quality fundamental seed laser. This results in a high degree of stability and control of the central wavelength, bandwidth, energy and duration of the output pulse. Since the duration of the HGHG radiation reflects the seed pulse characteristics, the output radiation pulse can be made shorter than the electron bunch length by simply utilizing an appropriate duration seed laser pulse synchronized to the electron beam. In fact, high peak power output pulses of a few femtoseconds are possible using chirped pulse amplification (CPA). On the other hand, a short SASE pulse requires an equally short electron bunch, which is presently beyond the state of the art below a few hundred femtoseconds. More problematic is that the temporal profile of the SASE output varies due to the uncontrollable statistical fluctuations of the shot noise that provides the starting signal, and the SASE output is not Fourier transform limited, but a superposition of many wave trains with phases determined by individual electrons.

Program's Objectives:

The objective was the measurement of the single pass FEL known as the High-Gain, Harmonic Generation FEL. The HGHG approach utilizes a laser-seeded FEL to produce amplified, longitudinally coherent, Fourier-

20010529 043

transform-limited output at a harmonic of the seed laser. In the experiment performed at the Accelerator Test Facility at Brookhaven National Laboratory, a seed CO₂ laser at a wavelength of 10.6mm produced saturated, amplified FEL output at the second-harmonic wavelength, 5.3mm. The experiment verifies the theoretical foundation for the HGHG FEL and prepares the way for the application of this technique in the vacuum ultraviolet, with the ultimate goal of extending the approach to provide an intense, highly coherent source of hard x-rays.

S&T Completed:

The HGHG FEL was demonstrated successfully. The duration of the output pulse was measured using a second-harmonic intensity autocorrelator, and the coherence length was measured using an interferometer. We also measured the energy distribution of the electron beam after it exited the second undulator, observing behavior consistent with that is expected at saturation. The intensity of the harmonic components of the output at 2.65 mm and 1.77 mm were determined relative to that of the 5.3-mm fundamental. Finally, using a corrector magnet upstream of the radiator, steering effects on the trajectories of the electron and light beams were studied.

Relevance:

The invention of the laser provided a revolutionary source of coherent light that created many new fields of scientific research. Modern laser technology provides versatile performance throughout much of the electromagnetic spectrum. Optical resonators exist in the infrared, visible, and ultraviolet regions of the spectrum, while nonlinear optics is used to extend coverage towards shorter wavelengths (<200 nm). However, the small nonlinear susceptibilities available at short wavelengths result in inefficient photon up-conversion. Thus, an important objective in optical physics is the development of coherent, intense sources at short wavelengths. Work to accomplish this is proceeding in several directions. In particular, there have been advances in high harmonic and x-ray sources generated from intense laser-atom interactions, and in development of plasma lasers (3). However, in the hard x-ray regime (1 Å), the free-electron laser (FEL) emerges as a promising source capable of producing unprecedented intensities. Like synchrotron radiation sources, FELs are based upon accelerator technology. FELs represent an advance over synchrotron radiation, because in an FEL the radiation process benefits from multi-particle coherence, while synchrotron radiation is emitted incoherently, by independently radiating electrons. Consequently, FELs offer the possibility of combining the intensity and coherence of a laser with the broad spectral coverage of a synchrotron.

References:

L.-H. Yu, M. Babzien, I. Ben-Zvi, L.F. DiMauro, A. Doyuran, W. Graves, E. Johnson, S. Krinsky, R. Malone, I. Pogorelsky, J. Skaritka, G. Rakowsky, L. Solomon, X.J. Wang, M. Woodle, V. Yakimenko, S.G. Biedron, J.N. Galayda, E. Gluskin, J. Jagger, V. Sajaev, I. Vasserman, High-Gain Harmonic-Generation Free-Electron Laser, *Science*, **289** (2000) 932.

Li-Hua Yu, Marcus Babzien, Ilan Ben-Zvi, Adnan Douryan, Bill Graves, Erik Johnson, Sam Krinsky, Robert Malone, Igor Pogorelsky, John Skaritka, George Rakowsky, L. Solomon, Xijie Wang, Marty Woodle, Vitaly Yakimenko, Sandra Biedron, John Galayda, Isaac Vasserman and Vadim Sajaev, The Status of the High-Gain Harmonic Generation Free-Electron Laser Experiment at the Accelerator Test Facility, *Proc. of the 1999 Particle Accelerator Conference*, A. Luccio, W. MacKay, Editors, 2471, (1999)

L.-H. Yu, M. Babzien, I. Ben-Zvi, L.F. DiMauro, A. Douryan, W. Graves, E. Johnson, S. Krinsky, R. Malone, I. Pogorelsky, J. Skaritka, G. Rakowsky, L. Solomon, X.J. Wang, M. Woodle, V. Yakimenko, S.G. Biedron, J.N. Galayda, E. Gluskin, J. Jagger, V. Sajaev, and I. Vasserman, First Lasing of a High-Gain Harmonic Generation Free-Electron Laser Experiment, *Nucl. Instru. Meth. A* **445**, (2000) 301

Doyuran, M. Babzien, T. Shafan, L.-H. Yu, I. Ben-Zvi, L. F. DiMauro, W. Graves, E. Johnson, S. Krinsky, R. Malone, I. Pogorelsky, J. Skaritka, G. Rakowsky, X.J. Wang, M. Woodle, V. Yakimenko, S. G. Biedron, J.N. Galayda, E. Gluskin, J. Jagger, V. Sajaev, I. Vasserman,
NEW RESULTS OF THE HIGH-GAIN HARMONIC GENERATION FREE- ELECTRON LASER EXPERIMENT,
Proceedings of 2000 International FEL Conference, Duke University August 14-18, 2000

Q: Other Sponsored Science & Technology:

A: Title: Accelerator Test facility Operations. Sponsoring agency: Department of Energy. Total funding: \$14.5M by FY01. Start date of the award: 10/1/88. End date of the award: NA. The BNL Accelerator Test Facility is a Users facility for research in Advanced Accelerator Concepts and the interaction of high-brightness electron beams and high-power, coherent electromagnetic radiation. The objective is to serve users in national laboratories, universities and industry and allow the development of better particle accelerators and coherent radiation sources.